


Diesel Generator Set

LG16.5SC

Powered By SDEC

50 Hz / 1500 RPM



MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310

Tel: +66 02 168 3193-5 #109 Fax: +66 02 168 3192

Email: marketing@multiphase-corp.com Website: www.multiphase-power.com

Facebook: www.facebook.com/MultiphasePower Line ID: @multiphasepower



LG16.5SC

| MODEL | FREQUENCY / RPM | STANDBY POWER | PRIME POWER |
|-----------------------------|-----------------|---------------|-------------|
| LG16.5SC Powered by SDEC | 50 Hz/1500 RPM | 16.5 kVA | 15 kVA |
| | | 13.2 kW | 12 kW |

- Model : MPLxxCS – S Suffix for silent type

| General Technical Data | |
|---------------------------------------|-----------------|
| Model | LG16.5SC |
| Engine | SDEC 4Z2.3-G11 |
| Standard Voltage | 400/230V |
| Phase | 3 Phase |
| Stamford Alternator | PI144D |
| Leroy Somer Alternator | TAL-A40-D |
| Other Alternator | Leega LA164G128 |
| Speed Control Type | Mechanical |
| Controller Model | DSE6120 |
| Generator Set Fuel Consumption (L/hr) | |
| Load-Standby Power (110%) | 5.1 |
| Load-Prime Power (100%) | 4.68 |
| Load-Prime Power (75%) | 3.6 |
| Load-Prime Power (50%) | 2.6 |

Multiphase Power Generators are in conformity with certification ISO 9001/ ISO14001/ISO18001 and our gensets are compliant with CE Standard. Best quality of electricity, high starting and loading capacity according to ISO8528-5. Ambient conditions of reference according to ISO 8528-1:2018 normative: 1000 mbar, 25°C, 30% relative humidity.

Prime Power (PRP):

According to ISO 8528-1:2018, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24 h of operation shall not exceed 70 % of the PRP.

Emergency Standby Power (ESP):

According to ISO 8528-1:2018, Emergency standby power is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP

Continuous Power (COP):

According to Standard ISO 8528-1:2018, this is the maximum power available for continuous loads for unlimited running hours a year between the maintenance times recommended by the manufacturer under the environmental conditions established by the same.

| Generator Set Ratings | | | | | | |
|-----------------------|-------|----------------|------|------|--------------|----|
| Voltage | Phase | Standby Rating | | | Prime Rating | |
| | | KVA | KW | AMPS | KVA | KW |
| 415/240v | 3 | 16.5 | 13.2 | 23.0 | 15 | 12 |
| 400/230v | 3 | 16.5 | 13.2 | 23.8 | 15 | 12 |
| 380/220v | 3 | 16.5 | 13.2 | 25.1 | 15 | 12 |

Operating Environmental Requirement

- Ambient Temperature : -25°C - 50°C (Heater must be included when in low temperature)
- Humidity: Less than 80%
- Altitude: Up to 1000meters (For higher altitude application, please consult with Our Team)


MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310 Tel: +66 02 168 3193-5
Website: www.multiphase-power.com Line ID: @multiphasepower



DIMENSIONS

| Weight And Dimensions | Open Type | Silent Type |
|---------------------------|-----------|-------------|
| Length (mm) | 1600 | 1900 |
| Width (mm) | 730 | 900 |
| Height (mm) | 1310 | 1205 |
| Net Weight (kg) | 600 | 800 |
| Fuel Tank Capacity (L) | 140 | 80 |
| Running Hours - 100% Load | 29.9 | 17.1 |



DIESEL ENGINE SPECIFICATION

| | | | | |
|----------------------------------|---------------------|----------------------------------|----------------------|--------------------|
| Manufacturer | SDEC | Engine Design | Standby Power | Prime Power |
| Engine Model | 4Z2.3-G11 | Gross Engine Output (KW) | 18 | 16 |
| Cylinders No./Arrangement | 4 / In-Line | Intake System (kPa) | Initial 3 / Final 4 | |
| Compression Ratio | 18:1 | Exhaust System (kPa) | Max 10 | |
| Injection Type | Direct | Water Flow (L/min) | n/a | |
| Aspiration Type | Naturally Aspirated | Air Flow (m³/min) | 1.7 | |
| Bore x Stroke | 85x100 mm | Exhaust Gas Flow (m³/min) | 7.2 | |
| Displacement | 2.3 L | Exhaust Gas Temp (°C) | 480 | |

MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310 Tel: +66 02 168 3193-5
Website: www.multiphase-power.com Line ID: @multiphasepower



| Diesel Engine Specifications | | |
|------------------------------|---------------------------------------|---------------------------------|
| Lubrication System | Lub. Method | Fully forced pressure feed type |
| | Oil Filter | Full Flow, Cartridge Type |
| | Oil pan capacity (High/Low) (L) | 10/8 |
| Fuel System | Injection pump | Kangda |
| | Governor | Electric type |
| | Opening pressure(kg/cm ²) | 24 |
| | Fuel filter | Full Flow, Cartridge Type |
| Cooling System | Coolant Capacity - Engine Only (L) | 2.7 |
| | Lid Min. pressure (kPa) | 70 |
| | Water Pump Capacity (L/min) | 25 |
| | Thermostat Range (°C) | 72-82 |
| | Cooling air flow (m ³ /s) | n/a |
| Electrical System | Charging Generator (V~A) | 12x70 |
| | Start Motor (V~kW) | 12x3.8 |
| | Battery voltage (V) | 12 |

ALTERNATOR SPECIFICATION

| | |
|----------------------|-------------------------|
| Poles | 4 |
| Insulation | Class H |
| Protection Rating | IP23 |
| Exciter System | Self-Excited, Brushless |
| AVR Regulation Range | ±1% |
| Number Of Bearing | Single Bearing |
| Coupling System | Flexible Disc |
| Winding Pitch | 2/3 |
| Overspeed Protection | 2250 R.P.M. |

ALTERNATOR STANDARD FEATURES

- All models are brushless, rotating-field alternators
- Alternator meet the main international standard of IEC 60034, NEMA MG 1.32-33, BS 5000 Part 99, VDE 0530, ISO 8528/3
- The AVR voltage regulator provides superior short circuit capability
- Self-ventilated and dip proof construction
- Superior voltage waveform

Note: See Alternator Data Sheets for application data and ratings, efficiency curves, voltage dip with motor starting curves, and short circuit decrement curves

MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310 Tel: +66 02 168 3193-5
Website: www.multiphase-power.com Line ID: @multiphasepower



CONTROL SYSTEM DATA (DSE6120)



Main Feature

The DSE 6120 is an Auto Mains (Utility) Failure Control Module developed to provide a wide range of operating and monitoring features for single diesel and gas gen-sets.

Key Function

- Support for 0-10 V & 4-20mA oil pressure senders
- Heated display option
- 3-phase generator sensing
- 3-phase mains (utility) monitoring
- Generator/load current monitoring & protection
- Configurable analogue/digital inputs (9)
- Configurable DC, volt-free and staged loading outputs (6)
- CAN, MPU & alternator speed sensing (selectable depending on engine type)
- DSE Configuration Suite PC Software
- Fuel and start outputs (configurable on CAN)
- Start on low battery
- Provides true generator sensing
- Provides true generator and mains (utility) sensing
- Provides multiple installation options
- Provides full generator load control
- Provides convenience of monitoring and protection of the generator or monitoring of the load current
- Provides complete user-friendly configuration and easy-to-use high-level system control & monitoring
- Ensures the display continues to operate in extreme cold weather conditions
- Provides flexibility for use with multiple sensors and engine types
- Enhanced alarm functionality
- Low load alarm
- Provides complete user-friendly configuration and easy-to-use high-level system control & monitoring

MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310 Tel: +66 02 168 3193-5
Website: www.multiphase-power.com Line ID: @multiphasepower



OPTIONAL

| Genset Optional Specifications | |
|--------------------------------|--|
| Engine | Water Jacket Pre-Heater |
| | Oil Pre-Heater |
| | Fuel-Water Separator |
| Alternator | Winding and Bearing Temperature Detector (RTD) |
| | Anti-Condensation Heater (Space Heater) |
| | PMG / AREP |
| | Anti-Damp and Anti-Corrosion Treatment |
| Electrical System | ATS |
| | Remote Control and Monitoring |
| | Synchronizing System |
| | 3/5 Pin sockets with RCBO protection |
| Fuel System | Bunded Double Wall Base Fuel Tank |
| | Extended To Larger Capacity Base Tank |
| | Free-stand Daily Fuel Tank |
| | Automatic Fuel Feeding System |
| | Fuel T-valves |
| Canopy | Trailer |
| | Rental Type Design |

| Optional Controller Model | |
|--|---------------------------|
| ComAp Controller for Single Genset Application | ComAp Nano MRS3 |
| | ComAp AMF20 |
| | ComAp AMF25 |
| ComAp Controller for Multi Genset Application | ComAp IG200 |
| | ComAp IG-NT |
| Deepsea Controller for Single Genset Application | DSE4520 MKII |
| | DSE6020 MKII |
| | DSE7320 MKII /DSE7420MKII |
| Deepsea Controller for Multi Genset Application | DSE8610 MKII |
| | DSE8810 MKII |

MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310 Tel: +66 02 168 3193-5
Website: www.multiphase-power.com Line ID: @multiphasepower

